



# 153

1500 lbs (680 kg) Capacity

<b>Performance:</b>	
Operating Capacity	680 kg
Tipping Load	1360 kg
Travel Speed	9.7 km/h
Breakout Force	1882 kg
Shipping Weight	2268 kg
Operating Weight	2504 kg

  

<b>Engine:</b>	
Make	Kubota
Model	V2203E
Power, ISO Net kW	34.3 (46) Net hp
Torque	15.9 kg
Displacement	2197 cc
Number of Cylinders	4
Rated Engine Speed, RPM	2800
Cooling System	Liquid
Fuel Type	Diesel No. 2D
Fuel Capacity, ()	64 Liters
Engine-to-Pump Connection	Double Universal Joint

  

<b>Electrical:</b>	
Ignition	12-Volt
Battery, C.C.A.	730
Alternator, amps	40
Remote Boosting Terminal Standard	Yes

**Controls/Drive System:**

Steering Controls	2 Hand Levers
Hydraulic Controls	2 Hand Levers or 2 Pedals
Transmission	Hydrostatic
Drive Chain Size	No.100

**Hydraulics:**

Hydraulic Pump Output	62.8 l/m
System Relief Pressure	165.5 BAR
Number of Bucket Cylinders	2
Breakout Force	1882 kg
Boom Mounted Aux, Hyds. Standard	Yes
Filtration	5 Micron
Hydraulic Oil Cooler	711 kj
Hyd. Reservoir Capacity	30.3 L

**Operator comfort & safety:**

Low Cab Sound Levels	Yes
Seat Bar Activated Parking Brake	Yes
Work Lights Standard	Yes
ROPS/FOPS Cab	Yes
Protective Seat Bar	Yes
Hydraulic Controls Lock (seat, seat belt & seat bar switch)	Yes
Cab-Operated Boom Supports	Yes
Top & Rear Window Glass Standard	Yes
Loader Frame Mounted Lifting Lugs	Yes
Loader Transportation Tie Downs	Yes