



165

1650 lbs (748 kg) Capacity

Performance:

Operating Capacity	748 kg
Tipping Load	1497 kg
Travel Speed	11.3 km/h
Breakout Force	1882 kg
Shipping Weight	2495 kg
Operating Weight	2675 kg

Engine:

Make	Turbo Cummins
Model	A2300T
Power, ISO Net kW	56 Net hp
Torque	18.7 kg
Displacement	2296 cc
Number of Cylinders	4
Rated Engine Speed, RPM	2800
Cooling System	Liquid
Fuel Type	Diesel
Fuel Capacity, ()	76 Liters
Engine-to-Pump Connection	Direct Coupling

Electrical:

Ignition	12 Volt
Battery, C.C.A.	730
Alternator, amps	60
Remote Boosting Terminal Standard	Yes

Controls/Drive System:

Steering Controls	Hydraulic Pilot Operated Joystick
Hydraulic Controls	Hydraulic Pilot Operated Joystick
Transmission	Hydrostatic
Drive Chain Size	No. 100

Hydraulics:

Hydraulic Pump Output	76.1 l/m
System Relief Pressure	172.4 BAR
Number of Bucket Cylinders	2
Breakout Force	1882 kg
Filtration	5 Micron
Hyd. Reservoir Capacity	75.7 L

Operator comfort & safety:

Work Lights Standard	Yes
ROPS/FOPS Cab	Yes
Protective Seat Bar	Yes
Hydraulic Controls Lock (seat, seat belt & seat bar switch)	Yes
Cab-Operated Boom Supports	No
Top & Rear Window Glass Standard	Yes
Loader Transportation Tie Downs	Yes