



175

1750 lbs (794 kg) Capacity

Performance:

Operating Capacity	794 kg
Tipping Load	1586 kg
Travel Speed	12.4 km/h
Breakout Force	1928 kg
Shipping Weight	2880 kg
Operating Weight	3175 kg

Engine:

Make	Kubota
Model	V2203T Turbo
Power, ISO Net kW	41.8 (56) Net hp
Torque	16.9 kg
Displacement	2000 cc
Number of Cylinders	4
Rated Engine Speed, RPM	2800
Cooling System	Liquid
Fuel Type	Diesel No. 2
Fuel Capacity, ()	73 Liters
Engine-to-Pump Connection	Double Universal Joint

Electrical:

Ignition	12-Volt
Battery, C.C.A.	730
Alternator, amps	40
Remote Boosting Terminal Standard	Yes

Controls/Drive System:	
Steering Controls	2 Hand Levers
Hydraulic Controls	2 Hand Levers or 2 Pedals
Transmission	Hydrostatic
Drive Chain Size	No.100

Hydraulics:	
Hydraulic Pump Output	62.8 l/m
System Relief Pressure	165.5 BAR
Number of Bucket Cylinders	2
Breakout Force	1928 kg
Boom Mounted Aux, Hyds. Standard	Yes
Filtration	5 Micron
Hydraulic Oil Cooler	xxx kj
Hyd. Reservoir Capacity	56 L

Operator comfort & safety:	
Low Cab Sound Levels	Yes
Seat Bar Activated Parking Brake	Yes
Work Lights Standard	Yes
ROPS/FOPS Cab	Yes
Protective Seat Bar	Yes
Hydraulic Controls Lock (seat, seat belt & seat bar switch)	Yes
Cab-Operated Boom Supports	Yes
Top & Rear Window Glass Standard	Yes
Loader Frame Mounted Lifting Lugs	Yes
Loader Transportation Tie Downs	Yes