



# 255

2500 lbs (1134 kg) Capacity

## Performance:

Operating Capacity	1134 kg
Tipping Load	2268 kg
Travel Speed	12.5 km/h
Breakout Force	3175 kg
Shipping Weight	3357 kg
Operating Weight	3629 kg

## Engine:

Make	Kubota
Model	V3300T Turbo
Power, ISO Net kW	61.9(83) Net hp
Torque	28.4 kg
Displacement	3318 cc
Number of Cylinders	4
Rated Engine Speed, RPM	2750
Cooling System	Liquid
Fuel Type	Diesel No. 2
Fuel Capacity, ()	109 Liters
Engine-to-Pump Connection	Direct Coupling

## Electrical:

Ignition	12-Volt
Battery, C.C.A.	1460
Alternator, amps	60
Remote Boosting Terminal Standard	Yes

<b>Controls/Drive System:</b>	
Steering Controls	2 Hand Levers
Hydraulic Controls	2 Hand Levers or 2 Foot Pedals
Transmission	Hydrostatic
Drive Chain Size	No.100H

<b>Hydraulics:</b>	
Hydraulic Pump Output	79.5 l/m
System Relief Pressure	206.8 BAR
Number of Bucket Cylinders	2
Breakout Force	3175 kg
Boom Mounted Aux, Hyds. Standard	Yes
Filtration	5 Micron
Hydraulic Oil Cooler	kj
Hyd. Reservoir Capacity	90 L

<b>Operator comfort &amp; safety:</b>	
Low Cab Sound Levels	Yes
Seat Bar Activated Parking Brake	Yes
Work Lights Standard	Yes
ROPS/FOPS Cab	Yes
Protective Seat Bar	Yes
Hydraulic Controls Lock (seat, seat belt & seat bar switch)	Yes
Cab-Operated Boom Supports	Yes
Top & Rear Window Glass Standard	Yes
Loader Frame Mounted Lifting Lugs	Yes
Loader Transportation Tie Downs	Yes