



# 85

850 lbs (386 kg) Capacity

### Performance:

Operating Capacity	386 kg
Tipping Load	816 kg
Travel Speed	8.1 km/h
Breakout Force	998 kg
Shipping Weight	1217 kg
Operating Weight	1353 kg

### Engine:

Make	Kubota
Model	D722B
Power, ISO Net kW	11.8 (15.8) Net hp
Torque	4.7 kg
Displacement	719 cc
Number of Cylinders	3
Rated Engine Speed, RPM	3200
Cooling System	Liquid
Fuel Type	Diesel No. 2D
Fuel Capacity, ()	55 Liters
Engine-to-Pump Connection	Double Universal Joint

### Electrical:

Ignition	12-Volt
Battery, C.C.A.	730
Alternator, amps	40
Remote Boosting Terminal Standard	Opt.

**Controls/Drive System:**

Steering Controls	2 Hand Levers
Hydraulic Controls	2 Foot Pedals
Transmission	Hydrostatic
Drive Chain Size	60H

**Hydraulics:**

Hydraulic Pump Output	30.3 l/m
System Relief Pressure	144.8 BAR
Number of Bucket Cylinders	2
Breakout Force	998 kg
Boom Mounted Aux, Hyds. Standard	Yes
Filtration	10 Micron
Hyd. Reservoir Capacity	43.0 L

**Operator comfort & safety:**

Low Cab Sound Levels	Yes
Seat Bar Activated Parking Brake	Yes
Work Lights Standard	Yes
ROPS/FOPS Cab	Yes
Protective Seat Bar	Yes
Hydraulic Controls Lock (seat, seat belt & seat bar switch)	Yes
Cab-Operated Boom Supports	Yes
Top & Rear Window Glass Standard	Yes
Loader Frame Mounted Lifting Lugs	Opt.
Loader Transportation Tie Downs	Yes