

▣ Specifications

▪ Machine weight

Canopy Rubber	kg	760
---------------	----	-----

▪ Standard bucket

Capacity	m ³	0.022
Width	mm	330

▪ Engine

Model		KUBOTA D722
Displacement	cc	719
Rated output/revolution	kW/min ⁻¹	7.4/2,000

▪ Working range

Max. digging depth	mm	1,550	
Max. vertical digging depth		1,140	
Max. digging height		2,835	
Max. dumping height		2,010	
Max. digging radius		2,840	
Min. turning radius		front	1,040
		swing	767
Rear slew radius		913	
Boom swing angle	deg.	L87°/R47°	

▪ Dimensions

Overall length	mm	2,913
Overall width		750(to)900
Overall height		2,052
Dozer blade(width×height)		700(or)900×200

- **Performance**

Travel speed	km/h	2.0
Slew speed	min ⁻¹	8.5
Gradeability	deg.	25°
Breakout force (Bucket)	kN	8.3
Breakout force (Arm)		5.9

- **Undercarriage**

Ground pressure - Canopy Rubber	kPa	21.1
Shoe width×tumbler center	mm	180×970
Type of traveling motor		Orbit
Crawler tension system		Thread type

- **Hydraulic System**

Type of hydraulic pump		Gear×2
Main pump oil flow qty.	ℓ/min	10.2×2
P.T.O. oil flow qty.		20.4
Main relief pressure	MPa	16.2×2

- **Others**

Hydraulic oil	ℓ	13.0
Engine oil		3.1
Fuel		9.0
Cooling water		3.8
Noise level Lwa/Lpa	dB	93/80

* 1PS=0.75kW