

## ▣ Specifications

### ▪ Machine weight

Canopy Rubber	kg	1,460
Canopy Steel		1,505
Cabin Rubber		1,570
Cabin Steel		1,620

### ▪ Standard bucket

Capacity	m <sup>3</sup>	0.04
Width	mm	400

### ▪ Engine

Model		mitsubishi L3E
Displacement	cc	952
Rated output/revolution	kW/min <sup>-1</sup>	12.5/2,400

### ▪ Working range

Max. digging depth	mm	2,175	
Max. vertical digging depth		1,535	
Max. digging height		3,250	
Max. dumping height		2,180	
Max. digging radius		3,730	
Min. turning radius		front	1,630
		swing	1,235
Rear slew radius		1,140	
Boom swing angle	deg.	L80°/R50°	

### ▪ Dimensions

Overall length	mm	3,720
Overall width		1,000
Overall height		2,260
Dozer blade(width×height)		1,000×240

- **Performance**

Travel speed	km/h	2.1/3.9
Slew speed	min <sup>-1</sup>	11.5
Gradeability	deg.	25°
Breakout force (Bucket)	kN	14.4
Breakout force (Arm)		9.0

- **Undercarriage**

Ground pressure	Canopy Rubber	kPa	26.0
	Cabin Rubber		28.0
Shoe width×tumbler center		mm	230×1,130
Type of traveling motor			Piston
Crawler tension system			Grease cylinder

- **Hydraulic System**

Type of hydraulic pump		Gear×3
Main pump oil flow qty.	ℓ/min	15.7×3
P.T.O. oil flow qty.		31.4
Main relief pressure	MPa	18.6×3

- **Others**

Hydraulic oil	ℓ	24.0
Engine oil		3.5
Fuel		20.0
Cooling water		5.6
Noise level Lwa/Lpa	dB	93/84

\* 1PS=0.75kW