

## ▣ Specifications

### ▪ Machine weight

Canopy Rubber	kg	2,080
Canopy Steel		2,130
Cabin Rubber		2,200
Cabin Steel		2,250

### ▪ Standard bucket

Capacity	m <sup>3</sup>	0.06
Width	mm	450

### ▪ Engine

Model		mitsubishi L3E
Displacement	cc	952
Rated output/revolution	kW/min <sup>-1</sup>	12.5/2,400

### ▪ Working range

Max. digging depth	mm	2,365	
Max. vertical digging depth		1,795	
Max. digging height		3,745	
Max. dumping height		2,510	
Max. digging radius		4,065	
Min. turning radius		front	1,745
		swing	1,405
Rear slew radius		1,255	
Boom swing angle	deg.	L80°/R50°	

### ▪ Dimensions

Overall length	mm	4,075
Overall width		1,380
Overall height		2,250
Dozer blade(width×height)		1,380×280

- **Performance**

Travel speed	km/h	2.2/3.8
Slew speed	min <sup>-1</sup>	11.5
Gradeability	deg.	30°
Breakout force (Bucket)	kN	16.3
Breakout force (Arm)		11.2

- **Undercarriage**

Ground pressure	Canopy Rubber	kPa	31.7
	Cabin Rubber		33.5
Shoe width×tumbler center	mm	230×1,325	
Type of traveling motor		Piston	
Crawler tension system		Grease cylinder	

- **Hydraulic System**

Type of hydraulic pump		Piston×2,Gear×1
Main pump oil flow qty.	ℓ/min	24.0×2+15.4
P.T.O. oil flow qty.		48.0
Main relief pressure	MPa	18.6×2/17.2

- **Others**

Hydraulic oil	ℓ	33.0
Engine oil		3.5
Fuel		29.0
Cooling water		5.6
Noise level Lwa/Lpa	dB	93/82

\* 1PS=0.75kW