

- **Machine weight**

Canopy Rubber	Kg	-
Canopy Steel		-
Cabin Rubber		5,350
Cabin Steel		5,400

- **Standard bucket**

Capacity	m <sup>3</sup>	0.16
Width	mm	650

- **Engine**

Model		KUBOTA V2403-DI
Displacement	cc	2,434
Rated output/revolution	kW/min <sup>-1</sup>	32.3/2,400

- **Working range**

Max. digging depth	mm	3,705	
Max. vertical digging depth		2,890	
Max. digging height		5,480	
Max. dumping height		3,735	
Max. digging radius		6,050	
Min. turning radius		front	2,550
		swing	1,970
Rear slew radius		980	
Boom swing angle	deg.	L70°/R55°	

- **Dimensions**

Overall length	mm	5,430
Overall width		1,980
Overall height		2,550
Dozer blade(width×height)		1,980×365

- **Performance**

Travel speed	km/h	2.6/4.2
Slew speed	min <sup>-1</sup>	9.5
Gradeability	deg.	27°
Breakout force (Bucket)	kN	42.8
Breakout force (Arm)		22.0

- **Undercarriage**

Ground pressure	Cabin Rubber	kPa	31.8
	Cabin Steel		32.1
Shoe width×tumbler center	mm	400×1,910	
Type of travel motor		Piston	
Crawler tension system		Grease cylinder	

- **Hydraulic System**

Type of hydraulic pump		Piston×1
Main pump oil flow qty.	ℓ/min	129.6
P.T.O. oil flow qty.		80.0
Main relief pressure	MPa	20.6

- **Others**

Hydraulic oil	ℓ	70.0
Engine oil		9.5
Fuel		70.0
Cooling water		7.8
Noise level Lwa/Lpa	dB	97/76