

Skid Steer Low Flow Flail Mulcher



Agrifuture is pleased to introduce the latest technology flail mulcher for Skid-Steers.

As you will see from the following material, Agrifuture certainly has the most advanced equipment available and suitable to work in the most rugged, inhospitable and remote areas.

Made of a structural steel housing, fine cut reversible knives, full width gauge roller with roller scraper, heavy duty bearing block and with the possibility to run with as little as 37 lts/min, "this mulcher is sure to please every contractor".

Mulching up to 25mm diameter, case drain is required.

Skid Steer Mulcher Standard Features

- Structural Steel Frame, Front & Rear
- 40mm Bearing on Gauge Roller
- Heavy-duty, Bearing Block
- 10 Gauge Hood
- 3-B Section Banded Belt
- 2190 RPM Rotor Speed
- 140mm OD x 6mm Wall Roller Tube
- 45mm Rotor Bearings
- Spring-loaded Belt Tightener
- 0 – 115mm Cutting Height
- Easy Access Belt Shield
- Full-width Gauge Roller with Roller Scraper
- Standard High-efficiency Gear-type Motor
- Universal Skid-steer Mount - Hydraulic-driven
- Fine-cut, Reversible Knives
- 6mm End Plates

Low Flow Skid Steer Flail Mulcher Images



Agrifuture Low Flow Skid Steer Flail Mulcher Specifications

AFP Code	AFP Description	Overall Width	Working Width	Cutting Tools	Weight
SF 180 LF	Skid Steer Mulcher Low Flow	183 cm	152 cm	80	422 Kg
SF 215 LF	Skid Steer Mulcher Low Flow	214 cm	183 cm	96	457 Kg
SF 260 LF	Skid Steer Mulcher Low Flow	259 cm	229 cm	120	548 Kg