



FasTrak™ 44/52 Specifications



Engine	OHV Honda	OHV Honda	OHV Honda	Kohler	Kohler
Model	OHV Honda	OHV Honda	OHV Honda	Kohler	Kohler
Horsepower	16	18	20	18	20
No. of Cylinders	2	2	2	1	1
Displacement	32.3 cu in (530 cc)	37.5 cu in (614 cc)	37.5 cu in (614 cc)	32.6 cu in (540 cc)	36.4 cu in (600 cc)
Compression Ratio	8:1	8.3:1	8.3:1	8.5:1	8.5:1
Max. Torque	26.9 ft lbs @ 2500 rpm	32.5 ft lbs @ 2500 rpm	32.5 ft lbs @ 2500 rpm	29.0 ft lbs @ 2800 rpm	32.0 ft lbs @ 2800 rpm
Models Available	16/44	18/44, 18/52	20/52	18/44	20/52

Electrical System 12 volt, 15 amp regulated

Ignition Electronic

Fuel Capacity 12.2 US gal (46.18 L)

Transmission Dual hydrostatic, Hydro-Gear IZT

Forward Speeds 0-7 mph (0-11.26 kph), infinitely variable

Reverse Speeds 0-5 mph (0-8 kph), infinitely variable

Steering Patented twin-lever, SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-degree-radius turns are all controlled with hand-operated controls (Patent # 6729115B2-FT)

Brakes

Service Hydrostatic dynamic braking

Parking Sprocket and cog. Patent-pending integral park brake system (when steering levers are placed in off position, park brakes are automatically engaged)

Seat Molded vinyl seat, deluxe high back. Standard armrests.

Accessories

Mulch Kit Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.

Catchers 6 bushel, rear-mounted, two-bag or side-mounted catchers available.

Light kit, hour meter

Snow Blower 48" two-stage blower utilizes the deck-lift to raise and lower. The blower is powered by deck belt and features a rotating chute adjustable from the seat and a heavy-duty gear box.

Snow Blade 56" wide, heavy-duty, reversible, replaceable cutting edge. Manual angling in 3 positions. Deck does not have to be removed to mount and use snow blade.

Specifications subject to change without notice.

Engine Model	OHV Honda	OHV Honda	OHV Honda	OHV Honda	Kohler	Kohler
Horsepower/Deck	16 hp/44	18 hp/44	18 hp/52	20 hp/52	18 hp/44	20 hp/52
Tires						
Front Casters	11 x 4 - 5, rib tread	11 x 4 - 5, rib tread	11 x 4 - 5, rib tread	11 x 4 - 5, rib tread	11 x 4 - 5, rib tread	11 x 4 - 5, rib tread
Rear Drive	18 x 8.50 - 8, turf tread	18 x 8.50 - 8, turf tread	18 x 9.50 - 8, turf tread	18 x 9.50 - 8, turf tread	18 x 8.50 - 8, turf tread	18 x 9.50 - 8, turf tread
Mower	44 in side-discharge	44 in side-discharge	52 in side-discharge	52 in side-discharge	44 in side-discharge	52 in side-discharge
Width	44 in (111.76 cm)	44 in (111.76 cm)	52 in (132.08 cm)	52 in (132.08 cm)	44 in (111.76 cm)	52 in (132.08 cm)
Blades	3, 15.7 in x 2.5 in x .20 in	3, 15.7 in x 2.5 in x .20 in	3, 18.3 in x 2.5 in x .20 in	3, 18.3 in x 2.5 in x .20 in	3, 15.7 in x 2.5 in x .20 in	3, 18.3 in x 2.5 in x .20 in
Blade Tip Speed	44 in - 17,100 fpm	44 in - 17,100 fpm	52 in - 17,600 fpm	52 in - 17,600 fpm	44 in - 17,100 fpm	52 in - 17,600 fpm
Cut Height	1 in to 4 in, .25 in increments (3.81 cm to 11.43 cm, .64 cm)	1 in to 4 in, .25 in increments (3.81 cm to 11.43 cm, .64 cm)	1 in to 4 in, .25 in increments (3.81 cm to 11.43 cm, .64 cm)	1 in to 4 in, .25 in increments (3.81 cm to 11.43 cm, .64 cm)	1 in to 4 in, .25 in increments (3.81 cm to 11.43 cm, .64 cm)	1 in to 4 in, .25 in increments (3.81 cm to 11.43 cm, .64 cm)
Dimensions						
Height	38 in (96.52 cm)	38 in (96.52 cm)	38 in (96.52 cm)	38 in (96.52 cm)	38 in (96.52 cm)	38 in (96.52 cm)
Length	65 in (165.10 cm)	65 in (165.10 cm)	69.62 in (176.83 cm)	69.62 in (176.83 cm)	65 in (165.10 cm)	69.62 in (176.83 cm)
Width Overall	49.2 in (124.97 cm)	49.2 in (124.97 cm)	57.2 in (145.29 cm)	57.2 in (145.29 cm)	49.2 in (124.97 cm)	57.2 in (145.29 cm)
Net Weight	730 lbs (331.12 kg)	730 lbs (331.12 kg)	740 lbs (335.67 kg)	740 lbs (335.67 kg)	745 lbs (337.92 kg)	755 lbs (342.46 kg)



For more information : www.hustlerturf.com

HUSTLER

HUSTLER TURF EQUIPMENT • HESSTON, KANSAS 67062 • 1-800-395-4757